



Privacy Information

We like to continuously improve our website and enable you to use it in the best possible way. For this, we work with our partners to improve your experience. You may opt-out at any time. For detailed information about personal information we collect and third parties having access to it, please select "More Information" or refer to our Privacy Policy.

[Legal Notice & Privacy Policy](#) [More Information](#)

Do not sell or share my personal information

OK

secure installation. Trifecta eliminates the need to purchase, install and adjust separate wheel end components and fasteners while maximizing reliability and uptime.

Trifecta Web Page (<http://www.stemco.com/product/trifecta-pre-adjusted-hub-assembly/>)

STEMCO TERRITORY REP MAP

Product Highlights

Simple Installation. Total Peace of Mind.

- Designed for fleets that value component longevity between service intervals and keeping time in the service bay as brief as possible, the Trifecta hub assembly represents the peak of durability and simplicity—the toughest, most resilient wheel end components united in an easy-to-install package.

Safety

- Provides quick and easy installation with no bearing adjustment required.
- Includes Zip-Torq® axle fastener featuring a unitized design with no additional clips, keepers, snap rings or screws, increasing simplicity for technicians.

Confidence

- Features industry-standard components manufactured by STEMCO & Webb Wheel.
- Backed by STEMCO support nationwide, including on-site training and certification, TMC-approved procedures and a 5-year/500,000 mile parts and labor OEM warranty.

Performance

- Discover® XR is a high-performance seal that provides quick and easy installation and long life. The seal ID includes patent-pending GlideLock™ technology, significantly reducing installation force by 50% with no prelube required—the first of its kind in the industry.
- The Discover XR seal utilizes a 4-zone labyrinth and slinger, combined with a Defender ESP™ hub cap, providing unmatched contamination exclusion.
- STEMCO manufactured precision bearings exceed ABMA performance and durability standards, and are included in OEM long-life wheel end systems.

Privacy Information

We like to continuously improve our website and enable you to use it in the best possible way. For this, we work with our partners to improve your experience. You may opt-out at any time. For detailed information about personal information we collect and third parties having access to it, please select "More Information" or refer to our Privacy Policy.

Legal Notice & Privacy Policy

Do not sell or share my personal information

Powered by Usercentrics Consent Management

STM 453 0137	453-0137	FF 5.44" TANG, 14.6 K, 2.74" WHEEL STUD , IRON HUB, W ABS
STM 453 0173	453-0173	R, 40 K, 3.15" WHEEL STUD , IRON LONG HUB, W ABS
STM 453 0236	453-0236	FF 5.44" DFLAT, 14.6 K, 3.19" WHEEL STUD , IRON HUB, W ABS
STM 453 0237	453-0237	FF 5.44" TANG, 14.6 K, 3.19" WHEEL STUD , IRON HUB, W ABS
STM 453 0273	453-0273	R, 40 K, 4.06" WHEEL STUD , IRON LONG HUB, W ABS

NOTE: Part numbers are available for truck & Trailer applications and are approved for oil bath applications only. Failure to run Trifecta wheel end systems with oil will result in loss of warranty.

General Product Information



Warranty Information

Features industry-standard components manufactured by STEMCO & Webb Wheel. Backed by STEMCO support nationwide, including on-site training and certification, TMC-approved procedures and a 5-year/500,000 mile parts and labor OEM warranty.

Last updated: Wednesday, 02 August 2023 02:28 PM

[▲ Back to Top](#)

Privacy Information

We like to continuously improve our website and enable you to use it in the best possible way. For this, we work with our partners to improve your experience. You may opt-out at any time. For detailed information about personal information we collect and third parties having access to it, please select "More Information" or refer to our Privacy Policy.

[Legal Notice & Privacy Policy](#)

Do not sell or share my personal information

Powered by Usercentrics Consent Management